



Broca de precisión HSS

Longitud [mm]	Velocidad de rotación rpm		Descripción	Nº artículo
Ø 4,1 mm				
55	1000	10	Broca S 4,1/55	9 250 405 000
Ø 4,5 mm				
60	900	10	Broca S 4,5/60	9 250 434 000
175	900	10	Broca S 4,5/175	9 250 436 000
235	900	10	Broca S 4,45/235	9 250 450 235
295	900	10	Broca S 4,5/295	9 250 450 295
Ø 5,0 mm				
60	900	10	Broca S 5,0/60	9 250 409 000
125	900	10	Broca S 5,0/125	9 250 411 000
220	900	10	Broca S 5,0/220	9 250 413 000
250	900	10	Broca S 5,0/250	9 250 414 000
Ø 5,1 mm				
62	900	10	Broca S 5,1/62	9 250 439 000
Ø 5,3 mm				
60	800	10	Broca S 5,3/60	9 250 415 000
125	800	10	Broca S 5,3/125	9 250 417 000
220	800	10	Broca S 5,3/220	9 250 419 000
290	800	10	Broca S 5,3/290	9 250 438 000
Ø 5,5 mm				
65	750	10	Broca S 5,3/65	9 250 420 000
125	750	10	Broca S 5,5/125	9 250 422 000
220	750	10	Broca S 5,5/220	9 250 423 000
290	750	10	Broca S 5,5/290	9 250 424 000
Ø 5,7 mm				
65	700	10	Broca S 5,7/65	9 250 425 000
125	700	10	Broca S 5,7/125	9 250 427 000
220	700	10	Broca S 5,7/220	9 250 429 000
290	700	10	Broca S 5,7/290	9 250 433 000
Ø 6,8 mm				
75	600	10	Broca S 6,8/75	9 250 430 000
225	600	10	Broca S 6,8/225	9 250 510 000
325	600	10	Broca S 6.8/325	9 250 680 325
Ø 7,0 mm				
125	600	10	Broca S 7,0/125	9 250 499 000
225	600	10	Broca S 7,0/225	9 250 493 000
325	600	10	Broca S 7.0/325	9 250 700 325
Ø 7,2 mm				
125	600	10	Broca S 7,2/125	9 250 504 000
225	600	10	Broca S 7,2/225	9 250 494 000
325	600	10	Broca S 7.2/325	9 250 720 325
Ø 7,4 mm				
125	600	10	Broca S 7,4/125	9 250 506 000
225	600	10	Broca S 7,4/225	9 250 497 000
325	600	10	Broca S 7.4/325	9 250 740 325

Rango de aplicación

| Para acero estructural

Propiedades

| Tipo S