


DEKTITE® Strip Flash Set



Application range

- > Sealing of wall joints
- > Forming expansion joints

Properties

- > Version TPE (grey)
- > Temperature resistance TPE (grey)
permanent 50 °C to +115 °C, short-term up to +150 °C
- > Edge of sealing strip ≤ 25 %
(accordion principle)
- > Use up to profile height ≤ 35 mm

Scope of delivery DS3 235


- 2 cartridges joint sealant
(neutral curing silicone)

Scope of delivery DS10 235

- 5 cartridges joint sealant
(neutral curing silicone)
- 1 self-drilling screw set

Scope of delivery DS15 450

- 10 cartridges joint sealant (neutral curing silicone)
- 1 self-drilling screw set




1. Do not mark the sealing line more than 75 mm above the purlin.




2. Apply sealant below the sealing line.




3. Trim of the DEKTITE®.




4. Fasten along the upper edge without stretching of the DEKTITE®.



5. Manually adjust DEKTITE® to the shape of the profiled sheet. Do not use tools!



6. Apply sealant.



7. Fasten to valley and to profile edges as shown.

Product online



| Order description | Length [m] | Width [mm] | Content Cartridge [ml] | Content screw [pieces] | PU [set] | Price/1 [EUR] | Article number | EAN |
|-------------------|------------|------------|------------------------|------------------------|----------|---------------|----------------|---------------|
| DS3 235 | 3.1 | 235 | 310 | 134 | 1 | | 8200006704 | 4061245013916 |
| DS10 235 | 10.0 | 235 | 310 | 410 | 1 | | 8200005704 | 4061245013930 |
| DS15 450 | 15.0 | 450 | 310 | 670 | 1 | | 8200002704 | 4061245013978 |